

tesa® 4101 PV2

Adhesive film of hydrate cellulose for packaging

PRODUCT INFORMATION

Product Description

tesa® 4101 PV 2 is based on a hydrate cellulose film coated with a rubber adhesive. The backing, which is composed of a sustainable material, is characterized by a high rigidity and low electrostatic charging. For this reason long strips of the tape can be dispensed without any curling effect is possible. The tape can easily be torn by hand.

Hydrate cellulose film can be cleanly cut (separated) by an subjacent tesa® tear strip.

Main Application

tesa® 4101 PV 2 is mainly used for general packaging purposes, such as sealing of small boxes. The tape can be easily applied with tesa® desk dispensers.

Technical Data

Backing material

hydrate cellulose

Adhesion to steel

6 N/cm 54.8 oz/in

Total thickness

51 µm 2 mils

Elongation at break

25 %

Type of adhesive

synthetic rubber

Tensile strength

42 N/cm 24 lbs/in

For latest information on this product please visit http://l.tesa.com/?ip=04101

Page 1 of 1 / As of 09/12/14

5825 Carnegie Boulevard Charlotte, NC 28209 Phone: 704 554 0707 Toll Free: 800 426 2181 Fax: 800 852 8831 customercare@tesatape.com Av. Santa Fe No. 170 German Centre P 6-3-3Col. Lomas de Santa Fe Mexico D.F. C.P. 01210 Phone: +52 (55) 5292 6978 Fax: +52 (55) 5292 6977

Technical Tape México S.A. de C.V.