

# tesa® 62872

Double-sided PE foam tape

PRODUCT INFORMATION

## Product Description

tesa® 62872 is a double-sided tape consisting of a PE foam backing and a pure acrylic adhesive.

tesa® 62872 features:

- High ultimate adhesive strength for secure bonding performance
- Conformable foam backing to compensate for design tolerances or uneven surfaces
- Excellent temperature resistance performance
- Excellent converting properties

## Technical Data

|                       |              |                      |                     |
|-----------------------|--------------|----------------------|---------------------|
| ■ Backing material    | PE foam      | ■ Tensile strength   | 8 N/cm              |
| ■ Color               | black        | ■ Type of liner      | 4.6 lbs/in          |
| ■ Total thickness     | 510 µm       | ■ Color of liner     | glassine            |
|                       | 20.1 mils    | ■ Thickness of liner | brown               |
| ■ Type of adhesive    | pure acrylic | ■ Weight of liner    | 71 µm               |
| ■ Elongation at break | 400 %        |                      | 2.8 mils            |
|                       |              |                      | 80 g/m <sup>2</sup> |

For latest information on this product please visit <http://l.tesa.com/?ip=62872>

Page 1 of 1 / As of 09/12/14

### tesa tape, inc.

5825 Carnegie Boulevard  
Charlotte, NC 28209  
Phone: 704 554 0707  
Toll Free: 800 426 2181  
Fax: 800 852 8831  
customer@tesatape.com

### Technical Tape México S.A. de C.V.

Av. Santa Fe No. 170  
German Centre P 6-3-3Col.  
Lomas de Santa Fe  
Mexico D.F. C.P. 01210  
Phone: +52 (55) 5292 6978  
Fax: +52 (55) 5292 6977

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, expressed or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to advise you.