

tesa® 53300

High Strength Tape for Low Energy Surfaces

PRODUCT INFORMATION

Product Description

tesa® 53300 is designed for low energy surfaces. It combines a mid-range tensile strength backing, with a high-performance synthetic rubber adhesive system.

tesa® 53300 has a mid-range thickness TPP backing in our assortment of LSE tapes, providing excellent ease of workability and sufficient conformability to surfaces, while providing a very secure bond between the adhesive and the surface.

The high-performance LSE synthetic rubber adhesive system provides a secure bond to difficult surfaces and removes cleanly off the surface without adhesive residue and filament delamination - a common problem with filament tape.

Available Colors: Blue

Suitable for holding and securing applications in the appliance industry.

Main Application

- Temporary holding of appliance parts
- Temporary holding on powder-coated surfaces
- Holding and securing of peripherals
- High-performance surface protection
- Holding and securing in the furniture industry
- Bundling of pipes
- Heavy duty unitizing and "L/C" clipping

Technical Data

■ Backing material	TPP	■ Adhesion to steel	7 N/cm
■ Total thickness	116.847 µm	■ Elongation at break	64 oz/in
	4.6 mils	■ Tensile strength	35 %
■ Type of adhesive	synthetic rubber		285 N/cm
			162.7 lbs/in

For latest information on this product please visit <http://l.tesa.com/?ip=53300>

Page 1 of 1 / As of 09/12/14

tesa tape, inc.

5825 Carnegie Boulevard
Charlotte, NC 28209
Phone: 704 554 0707
Toll Free: 800 426 2181
Fax: 800 852 8831
customer@tesatape.com

<http://www.tesatape.com>

Technical Tape México S.A. de C.V.

Av. Santa Fe No. 170
German Centre P 6-3-3Col.
Lomas de Santa Fe
Mexico D.F. C.P. 01210
Phone: +52 (55) 5292 6978
Fax: +52 (55) 5292 6977

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, expressed or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to advise you.