

HEAVY DUTY, TENSILIZED STRAPPING TAPE

TYPICAL APPLICATIONS

- Palletizing, banding, bundling, reinforcing and heavy duty strapping

ADVANTAGES AND BENEFITS

- Resists moisture and solvents
- Excellent abrasion resistance
- Specifically formulated, high memory film designed to contract when applied under firm manual tension



CONSTRUCTION

Overall Grade/Function: Heavy Duty
Backing: Tensilized, mono-oriented polypropylene film
Adhesive: Water-based acrylic

COLOR(S)



Clear (CLR)

STANDARD WIDTH(S)

1 in

STANDARD LENGTH(S)

60 yd

Contact your Shurtape sales representative for other available sizes.

PHYSICAL PROPERTIES

	STANDARD	METRIC
Tensile Strength	145 lbs/in width	253.9 N/10 mm
Adhesion to Stainless Steel	45 oz/in width	4.93 N/10 mm
Thickness	5 mils	0.13 mm
Elongation	30%	30%
Service Temperature Range	0 F to 250 F	-18 C to 121 C

Physical and performance characteristics shown above are obtained from tests recommended by PSTC, ASTM, government agencies or Shurtape Technologies, LLC, Quality Assurance and Technical Service Departments and do not represent a guarantee of product performance. Individual rolls may vary slightly from these averages. The user should determine whether the product is fit for a particular purpose and is suitable for the user's method of application before use.

STORAGE & USAGE CONDITIONS

Tape should be stored in its original packaging in a cool, dry area away from direct sunlight and should be used within 12 months of date of shipment. Surfaces to which tape is applied should be clean, dry and free of grease, oil or other contaminants.