

EV 57 COLORS

UL LISTED ELECTRICAL TAPE

TYPICAL APPLICATIONS

- Splice, insulate and bind wiring harnesses


ADVANTAGES AND BENEFITS

- High tensile strength and elongation
- Non-corrosive adhesive

CONSTRUCTION

Overall Grade/Function: UL Listed Electrical Tape
Backing: Matte finish, soft polyvinylchloride (SPVC)
Adhesive: Non-corrosive, natural rubber

COLORS

| | | | |
|--|--------------|---|--------------|
|  | Blue (BLU) |  | Orange (ORG) |
|  | Green (GRN) |  | Red (RED) |
|  | Brown (BRN) |  | White (WHI) |
|  | Yellow (YEL) |  | Purple (PRP) |



STANDARD WIDTH(S)

¾ in 19 mm

STANDARD LENGTH(S)

66 ft 20 m

Contact your Shurtape sales representative for other available sizes.

PHYSICAL PROPERTIES

| | STANDARD | METRIC |
|-----------------------------|-------------------|---------------|
| Tensile Strength | 12.6 lbs/in width | 22.07 N/10 mm |
| Adhesion to Stainless Steel | 13 oz/in width | 1.42 N/10 mm |
| Thickness | 6.8 mils | 0.17 mm |
| Elongation | 380% | 380% |
| Service Temperature Range | 20F to 176 F | -7 C to 80 C |

Physical and performance characteristics shown above are obtained from tests recommended by PSTC, ASTM, government agencies or Shurtape Technologies, LLC, Quality Assurance and Technical Service Departments and do not represent a guarantee of product performance. Individual rolls may vary slightly from these averages. The user should determine whether the product is fit for a particular purpose and is suitable for the user's method of application before use.

APPLICABLE STANDARDS

UL Listed for Insulation Tapes

STORAGE & USAGE CONDITIONS

Tape should be stored in its original packaging in a cool, dry area away from direct sunlight and should be used within 12 months of date of shipment. Surfaces to which tape is applied should be clean, dry and free of grease, oil or other contaminants.

*Shurtape® is a registered trademark of Shurtape Technologies, LLC

Form# TDS-EV-057-COL-11/20/2013