

LTS90B/G

Sealant tape

Ideally suited to wind energy applications

Features

- Specially formulated with a cost optimised design suitable for ambient, debulk and medium temperature applications.
- Widely used in the wind, marine and glass industries.
- Excellent tack.
- Also suitable for high temperature envelope bagging applications.
- Material compatible with most substrates (including composite tools) and film materials.
- For optimum results, tape must be allowed to cool to an ambient temperature before stripping from mould surfaces.

Product variants

- Black (LTS90B)
- Grey (LTS90G)

Properties

Maximum cure temperature	150°C bag to tool 180°C bag to bag	302°F bag to tool 356°F bag to bag
Colour	Black (LTS90B) Grey (LTS90G)	

Availability

Roll size	15m x 12mm x 3mm	49ft x 0.5in x 0.125in
	Also available as a 4mm (0.16in) diameter bead	
Standard box contents	22 rolls per box	

Storage

Must be stored in its original containers, under optimum conditions of between 5 and 25°C (41°F and 77°F).
Material has a 2 year shelf life from date of manufacture.

Must be stored flat.

Boxes should be stacked no more than 5 high.

Health & safety

Handling of these products must conform to individual company guidelines and health and safety regulations.

All statements, technical information and recommendations contained in this data sheet are given in good faith and are based on tests believed to be reliable, but their accuracy and completeness are not guaranteed. They do not constitute an offer to any person and shall not be deemed to form the basis of any subsequent contract. All products are sold subject to the Cytec's Standard Terms and conditions of Sale. Accordingly, the user shall determine the suitability of the products for their intended use prior to purchase and shall assume all risk and liability in connection therewith. It is the responsibility of those wishing to sell items made from or embodying the products to inform the user of the properties of the products and the purposes for which they may be suitable, together with all precautionary measures required in handling those products. The information contained herein is under constant review and liable to be modified from time to time.

© Copyright 2012 – Cytec Process Materials (Keighley) Ltd, Cytec Process Materials (CA) Inc, Cytec Process Materials (Toulouse) Sarl, Cytec Process Materials (Milan) Srl. All rights reserved worldwide. All trademarks or registered trademarks are the property of their respective owners.