

Poly1

Adhesive tape

Ideally suited to high temperature applications

Features

- High temperature polyimide tape.
- Used to hold down the consumable package on high temperature cure work.
- Can also be used to hold down the edge of bagging membrane to the tool surface, as most high temperature sealant tapes do not exhibit much tack at room temperature.

Properties

	260°C	500°F
Maximum cure temperature		
Colour	Amber	
Adhesive	Silicone	
Carrier	Nylon	
Total thickness	65µm	0.0026in
Adhesive thickness	40µm	0.0016in
Tape thickness	25µm	0.001in

Availability

	Up to 50mm	Up to 2in
Standard width		
Standard length	33m	36yd

Storage

No special storage conditions.

Health & safety

Handling of these products must conform to individual company guidelines and health and safety regulations.

All statements, technical information and recommendations contained in this data sheet are given in good faith and are based on tests believed to be reliable, but their accuracy and completeness are not guaranteed. They do not constitute an offer to any person and shall not be deemed to form the basis of any subsequent contract. All products are sold subject to the Cytec's Standard Terms and conditions of Sale. Accordingly, the user shall determine the suitability of the products for their intended use prior to purchase and shall assume all risk and liability in connection therewith. It is the responsibility of those wishing to sell items made from or embodying the products to inform the user of the properties of the products and the purposes for which they may be suitable, together with all precautionary measures required in handling those products. The information contained herein is under constant review and liable to be modified from time to time.

© Copyright 2012 – Cytec Process Materials (Keighley) Ltd, Cytec Process Materials (CA) Inc, Cytec Process Materials (Toulouse) Sarl, Cytec Process Materials (Milan) Srl. All rights reserved worldwide. All trademarks or registered trademarks are the property of their respective owners.